

Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Acetone

MSDS Number : 000000011657

Product Use Description : Solvent

Manufactured for : VWR International LLC

Radnor Corporate Center

Building One Suite 200

100 Matsonford Road Radnor PA 19087

For more information call : (Monday-Friday, 8.00am-5:00pm)

1-800-932-5000

In case of emergency call : (24 hours/day, 7 days/week)

1-800-424-9300(USA Only)

For Transportation Emergencies:

1-800-424-9300 (CHEMTREC - Domestic) 1-613-996-6666 (CANUTEC - Canada)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid, clear

Color : colourless

Odor : sweet mint-like

Page 1 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

GHS Label elements, including precautionary statements

Symbol(s)





Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

Causes eye irritation.

May cause respiratory irritation. May cause drowsiness and dizziness.

Precautionary statements : **Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

Call a POISON CENTER or doctor/ physician if you feel unwell.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam for extinction.

Storage:



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Store in a well-ventilated place. Keep container tightly closed.

Keep cool. Store locked up.

Disposal:

Dispose of contents/container in accordance with local, state &

federal regulations.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Formula : C3H6O

Chemical nature : Substance

	Chemical Name	CAS-No.	Concentration
Acatona		67-64-1	100.00.9/
Acetone		67-64-1	100.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15

minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician if

irritation develops or persists.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Call a physician.

Page 3 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Ingestion : Do not induce vomiting without medical advice. If a person

vomits when lying on his back, place him in the recovery position. Never give anything by mouth to an unconscious

person. Call a physician.

Notes to physician

Treatment : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Dry chemical

Foam

Carbon dioxide (CO2)

Cool closed containers exposed to fire with water spray.

Unsuitable extinguishing

media

: Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during

firefighting

: Extremely flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors. Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment. Unprotected persons

must be kept away.

Immediately evacuate personnel to safe areas.

Page 4 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Keep people away from and upwind of spill/leak.

Ensure adequate ventilation. Remove all sources of ignition.

Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

Methods for cleaning up : Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Wear personal protective equipment.

Use only in well-ventilated areas. Keep container tightly closed.

Do not smoke. Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Advice on protection against :

fire and explosion

Keep away from fire, sparks and heated surfaces.

Take precautionary measures against static discharges.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Use explosion-proof equipment.

Keep product and empty container away from heat and sources

of ignition.

Page 5 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

No sparking tools should be used.

No smoking.

Storage

Requirements for storage areas and containers

Store in area designed for storage of flammable liquids. Protect

from physical damage.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Keep away from heat and sources of ignition.

Keep away from direct sunlight.

Store away from incompatible substances.

Container hazardous when empty.

Do not pressurize, cut, weld, braze, solder, drill, grind or expose

containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : Use with local exhaust ventilation.

Prevent vapour buildup by providing adequate ventilation during

and after use.

Eye protection : Do not wear contact lenses.

Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Page 6 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Flame retardant antistatic protective clothing.

If splashes are likely to occur, wear:

Protective suit

: In the case of vapour formation use a respirator with an Respiratory protection

approved filter.

For rescue and maintenance work in storage tanks use

self-contained breathing apparatus.

Use NIOSH approved respiratory protection.

When using, do not eat, drink or smoke. Hygiene measures

Wash hands and face before breaks and immediately after

handling the product.

Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Exposure Guidelines						
Components	CAS-No.	Value	Control parameters	Upda te	Basis	
Acetone	67-64-1	TWA: time weighted average	(500 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values	
			1	_		
Acetone	67-64-1	STEL: Short term exposure limit	(750 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values	
Acetone	67-64-1	TWA: time weighted average	(250 ppm)	02 2014	ACGIHLIS_P:US. ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values	



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Acetone	67-64-1	STEL:	(500 ppm)	12	ACGIHLIS P:US.
	37 3	Short term exposure	(330 pp)	2010	ACGIH Notice of Intended Changes (NIC) to Threshold
		limit			Limit Values
Acetone	67-64-1	REL: Recomm ended exposure limit (REL):	590 mg/m3 (250 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Acetone	67-64-1	PEL: Permissi ble exposure limit	2,400 mg/m3 (1,000 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Acetone	67-64-1	TWA : time weighted average	1,800 mg/m3 (750 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
Acetone	67-64-1	STEL : Short term exposure limit	2,400 mg/m3 (1,000 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid, clear

Color : colourless

Odor : sweet mint-like

Page 8 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

pH : Note: Not applicable

Melting point/freezing point : -94.8 ℃

Boiling point/boiling range : 56 ℃

Flash point : $-4 \, ^{\circ}\text{F} (-20 \, ^{\circ}\text{C})$

Method: closed cup

Evaporation rate : 12

Method: Compared to Butyl acetate.

Lower explosion limit : 2 %(V)

Upper explosion limit : 13 %(V)

Vapor pressure : 240 hPa

at 20 °C(68 °F)

Vapor density : 2.0 Note: (Air = 1.0)

Density : 0.79 g/cm3 at 20 ℃

Water solubility : Note: completely soluble

Solubility in other solvents : Note: no data available

Partition coefficient: : Pow: 0.58 log Pow: -0.24

n-octanol/water

Page 9 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Ignition temperature : 465 ℃

Viscosity, dynamic : Note: no data available

Viscosity, kinematic : Note: no data available

Molecular weight : 58.05 g/mol

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

: Heat, flames and sparks.

Keep away from direct sunlight.

: Hazardous polymerisation does not occur.

Incompatible materials to

avoid

: Acids Aldehydes

Alkalis Amines Ammonia Oxidizing agents

Reducing agents
Chlorine compounds

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Page 10 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Acute oral toxicity : LD50: 5,800 mg/kg

Species: Rat

Acute inhalation toxicity : LC50: 32000 ppm

Exposure time: 4 h Species: Rat

Acute dermal toxicity : LD50: > 7,426 mg/kg

Species: Guinea pig

Skin irritation : Species: Rabbit

Result: Mild skin irritation Exposure time: 24 h

Eye irritation : Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Repeated dose toxicity : Species: Rat

NOEL: 19000 ppm

Note: 8-Week Inhalation Toxicity Study 5 days/week for 8 weeks Slightly reduced weight gain compared to controls

: Species: Rat

NOEL: 100 mg/kg/d

Note: 90-Day Oral Toxicity Study increased liver and kidney

weights

: Species: Rat

Lowest observed effect level: 500 mg/kg/d

Note: 90-Day Oral Toxicity Study increased liver and kidney

weights



Acetone

BDH1101

Revision Date 03/19/2015 Print Date 05/08/2015 Version 1.5

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

: LC50: 5,540 mg/l Toxicity to fish

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

: LC50: 8,300 mg/l Exposure time: 96 h

Species: Lepomis macrochirus (Bluegill sunfish)

Toxicity to daphnia and other : LC50: 10 mg/l

aquatic invertebrates

Exposure time: 24 h

Species: Daphnia magna (Water flea)

: EC50: 3,020 mg/l Toxicity to algae

Exposure time: 14 d

Species: Chlorella pyrenoidosa (aglae)

Toxicity to bacteria : LC50: > 1,000 mg/l

Species: Bacteria

Elimination information (persistence and degradability)

Biodegradability : anaerobic

Result: Readily biodegradable

Value: 78 %

Method: OECD 301 D

Further information on ecology



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Dispose of contents/ container in accordance with local, state,

and federal regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1090

Proper shipping name : ACETONE

Class 3 Packing group II Hazard Labels 3

IATA UN/ID No. : UN 1090

Description of the goods : ACETONE

Class : 3
Packaging group : II
Hazard Labels : 3
Packing instruction (cargo : 364

aircraft)

Packing instruction : 353

(passenger aircraft)

Packing instruction : Y341

(passenger aircraft)

IMDG UN/ID No. : UN 1090

Description of the goods : ACETONE

Class : 3
Packaging group : II
Hazard Labels : 3
EmS Number : F-E, S-D

Marine pollutant : no

SECTION 15. REGULATORY INFORMATION



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Inventories

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia, Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian **Environmental Protection**

Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL.

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control

: On the inventory, or in compliance with the inventory

Act

Chemical Substances

China. Inventory of Existing : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

National regulatory information

US. Drug Enforcement Administration (DEA) Listed Precursor and Essential Chemicals (21 CFR 1310)

: On the United States Drug Enforcement Authority (DEA) List of

Precursors and Essential Chemicals

1

: Acetone 67-64-1



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

SARA 302 Components : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313 Components : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard Chronic Health Hazard

CERCLA Reportable

Quantity

: 5000 lbs

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Massachusetts RTK : Acetone 67-64-1

New Jersey RTK : Acetone 67-64-1

Pennsylvania RTK : Acetone 67-64-1

WHMIS Classification : B2: Flammable liquid

D2B: Toxic Material Causing Other Toxic Effects

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required

by the CPR.

SECTION 16. OTHER INFORMATION

HMIS III NFPA

Health hazard : 2* 1

Page 15 / 16



Acetone

BDH1101

Version 1.5 Revision Date 03/19/2015 Print Date 05/08/2015

Flammability : 3 3
Physical Hazard : 0
Instability : 0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 06/20/2012

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group